

TSL LED EMERGENCY TWINHEAD LED (BOX STYLE)

- ❖ LED Source Non-Maintained Emergency Twinhead.
- ❖ Neutrik PowerCON True1 connection & loop through.
- ❖ Supplied as Standard with M12 Half Coupler
- ❖ Additional eye for secondary safety bond





Emergency Twinhead

Datasheet

TSL PART CODE	LED Emergency Twinhead LED (Black) (Box Style) - True 1
DESCRIPTION	230V IP20 LED Emergency Twinhead (non-maintained)
NET WEIGHT (KG)	0.60
FINISH	Black
DIMENSIONS (MM)	(L) 275 x (H) 110 x (D) 70
CONSTRUCTION	Folded Aluminium
CLASS	I
IP RATING	IP20
WATTAGE	6
LAMP TECHNOLOGY	SMD LED
LUMENS (LM)	219
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	36.5
CIRCUIT WATTAGE (W)	6.00
CCT	6000k (Daylight)
LIFESPAN (HRS)	40,000
DIMMABLE	No
EMERGENCY	Non-maintained
OPERATING TEMPERATURE	0-45°C
INPUT VOLTAGE	230V 50HZ
WARRANTY	2 Years
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598-2-22
ORIGIN OF PARTS MANUFACTURE	CN
ASSEMBLED IN	UK
EAN	FAT-ZFZD-E6W



